

CASTING C 150

Insulation classClass IIBeam angle86°MountingGround

Lamps description Power Led: 12W - 1080 lm ≠ FIXT 565 lm - 2700K/CRI 80 - 110-240V

Environment Outdoor

Notes We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

Technical description The body of the versions C and T is made of extruded


aluminum, base and diffuser in die-cast aluminum EN AB-47100 with a low copper content. High-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. A glass diffuser is glued to the heat sink of the product to ensure a watertight seal, micro-texturized to ensure homogeneous and uniform distribution of the light. The luminaire is provided with a segment of outgoing cable in neoprene. We recommend installation on a plinth of cement or on a flat surface.




Casting C 150

designed by Vincent Van Duysen

Collection of outdoor bollard lights with LED light source. I 10/240V power supply integrated.



DIMENSIONS



CERTIFICATIONS














ELECTRICAL

Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 110/240

PHYSICAL

IK rating06AimingFixedWeight (kg)3,30Number of headsI





Casting C 150 . Accessories

Electrical



F1206000

3/4 way terminal block 3 poles IP68

7-12 mm cables




Casting C 150

designed by Vincent Van Duysen

Collection of outdoor bollard lights with LED light source. I I 0/240V power supply integrated.

F1230001 White
F1230006 Grey
F1230033 Anthracite
F1230030 Black
F1230018 Deep Brown

DIMENSIONS



CERTIFICATIONS








IP 65







Casting C 150 . Accessories

Structural



F1207000

Base plate with bolt

Casting C 150. Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:


Power LED




Casting C 150

designed by Vincent Van Duysen

Collection of outdoor bollard lights with LED light source. I I 0/240V power supply integrated.



DIMENSIONS



CERTIFICATIONS











