

#### MY WAY 110X100

Insulation classClass IBeam angle74°

Mounting Wall surface

Lamps description Mid-Power Led: 5W - 490 lm ≠ FIXT 211 lm - 3000K/CRI 80 -

100-240V

**Environment** Indoor, Outdoor

**Notes** We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

**Technical description** Aluminum die-cast body EN AB-47100 (low copper

content). High-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to

protect against oxidation. Frosted polycarbonate diffuser, UV-stabilised, glued to the head of the product to ensure a

watertight seal.



Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 100/240

#### **PHYSICAL**

Aiming Fixed
Weight (kg) 0,52
Number of heads I




#### My Way 110x100

designed by Piero Lissoni

Luminaire for outdoor use for built-in installation on the wall with LED light source. Integrated 110/240V power source. Supplied with a 120 mm section of outgoing neoprene cable and IP67 cable connection system.

F4351001 White
F4351006 Grey
F4351033 Anthracite
F4351030 Black
F4351018 Deep Brown

#### **DIMENSIONS**




### **CERTIFICATIONS**















# My Way 110x100 . Accessories

### **E**lectrical



F990C00A000

2 way terminal block 3 poles IP68

7-12 mm cables




## My Way 110x100

designed by Piero Lissoni

Luminaire for outdoor use for built-in installation on the wall with LED light source. Integrated 110/240V power source. Supplied with a 120 mm section of outgoing neoprene cable and IP67 cable connection system.

F4351001	White
F4351006	Grey
F4351033	Anthracite
F4351030	Black
F4351018	Deep Brown

### **DIMENSIONS**




### **CERTIFICATIONS**











## My Way 110x100 . Accessories

#### Mounting



122 70 22 **1**2 **1** 

F4301000

**Remote Housing** 

## My Way 110x100. Lamps



#### **Mid-Power LED**

Lamp category:

LED

Socket:

Special base

Lamp type:


Power LED




### My Way 110x100

designed by Piero Lissoni

Luminaire for outdoor use for built-in installation on the wall with LED light source. Integrated 110/240V power source. Supplied with a 120 mm section of outgoing neoprene cable and IP67 cable connection system.



### **DIMENSIONS**



### **CERTIFICATIONS**









