


Ray Floor 2

by Rodolfo Dordoni, 2006



Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.







Mounting Floor
Environment Indoor

Finish White, Glass, Black
Weight 6.2 (met) - 9.2 (glass) Kg

Light sources 1 x LED 21W E27 2452lm 3000K [e] cod. available RF26998 DIMMER

Emergency Without

Switching On the cable there is the electronic dimmer

which allows the regulation of light brightness

with a dial.

 Voltage
 220-240V

 Power
 MAX 250W

Battery No Supply included Yes

Cord Length 1900 mm

Materials Aluminum, Glass, Steel

Colors F5921030 - Black F5921009 - White

F5920020 - Glass

Certificate (€ 🐠 🕌 🔲